



## FTXA-A/B (W/S/T/B) / RXA-A/B **R-32** BLUEEVOLUTION

### Award winning design

Stylish brings together excellent design and technology to deliver a total climate solution for any interior. Measuring only 189mm deep, Stylish is one of the slimmest wall mounted units on the market and achieves the best in comfort, energy efficiency, reliability and control.

Inspired by its predecessors, Daikin Emura and Ururu Sarara, Stylish has earned the Good Design Award for its innovative look and functional capabilities.

Users can now choose from **four distinct colours** (white, silver, blackwood and now matt black).

- > **Curved corners** create an unobtrusive and space-saving design
- > Simple panel enables variation in texture and colour to easily blend into any room

### The Coanda effect

Already present in the Ururu Sarara, the **Coanda effect** optimises the airflow for a comfortable climate. By using specially designed louvres, a more focused airflow allows a better temperature distribution throughout the whole room.



### How it works

Stylish determines the airflow pattern based on whether the room needs heating or cooling. When Stylish is in heating mode, two louvres will direct air downward (vertical airflow), while in cooling mode the louvres will move air upward (ceiling airflow).

By creating two different airflow patterns, Stylish prevents draughts and establishes a more stable and comfortable room temperature for occupants.

### Fresh, pure air

Stylish provides the best indoor air quality using **Daikin's Flash Streamer** technology. This system removes particles, allergens and odours to deliver healthy indoor air.

### Quiet operation

Stylish uses a **newly designed fan** to optimise airflow for higher energy efficiency at low sound levels. To achieve higher energy efficiency, Daikin designed a new fan that runs efficiently within Stylish's compact dimensions. Together, the fan and heat exchanger attain top energy performance but operate at a sound level that is practically inaudible to occupants.



FTXA-AW



FTXA-BB



FTXA-BS



FTXA-BT



RXA-A/B



ARC466A58



WI-FI ADAPTOR

INCLUDED AS STANDARD



# FTXA-A/B (W/S/T/B) / RXA-A/B

**I-32** BLUEEVOLUTION

Indoor Units	White	CTXA15AW	FTXA20AW	FTXA25AW	FTXA35AW	FTXA42AW	FTXA50AW
	Black	CTXA15BB	FTXA20BB	FTXA25BB	FTXA35BB	FTXA42BB	FTXA50BB
	Silver	CTXA15BS	FTXA20BS	FTXA25BS	FTXA35BS	FTXA42BS	FTXA50BS
	Blackwood	CTXA15BT	FTXA20BT	FTXA25BT	FTXA35BT	FTXA42BT	FTXA50BT
Capacity	UK Total Cooling	kW					
	UK Sensible Cooling	kW					
	Nominal Cooling	kW					
	Nominal Heating	kW					
Seasonal Efficiency (EN14825) COOLING	Energy Label	Multi Combination Only					
	Pdesign	kW					
	SEER						
	Annual Energy Consumption	kWh					
Seasonal Efficiency (EN14825) HEATING	Energy Label	Multi Combination Only					
	Pdesign	kW					
	SCOP						
	Annual Energy Consumption	kWh					
Nominal Efficiency	EER/COP						
Air Flow Rate (Cooling)	High / Nom / Low / Silent	m³/sec					
Dimensions	Height / Weight / Depth	mm					
Weight		kg					
Sound Pressure (Cooling)	High / Nom / Low / Silent	dbA					
Sound Power (Cooling)		dbA					
Outdoor Units			RXA20A	RXA25A	RXA35A	RXA42B	RXA50B
Dimensions	Height x Width x Depth	mm					
Weight		kg					
Electrical Details	Power Supply						
	Running Current	A					
	Starting Current	A					
	Max Fuse Size	A					
Interconnection Wiring	Core / Cable Size						
Piping Connections	Liquid / Gas	inches (mm)					
Pipework	Maximum Length	m					
	Maximum Vertical Rise	m					
	Precharged to	m					
	Additional charge	g/m					
	Holding charge	kg					
Sound Pressure (Cooling)	High	dbA					
Sound Power (Cooling)		dbA					
Operating Range (Cooling)	Min / Max	°CDB					
Operating Range (Heating)	Min / Max	°CWB					
ECA Eligible							

## Accessories:

Accessory Ref	Description
EKRS21	Wire harness for new S21 port for all marked (*) options
BRC073*	Optional wired remote controller BRC1E53 style - Connection cable required
BRCW901A03	3m connection cable for BRC073
BRCW901A08	8m connection cable for BRC073
K.CGM	Condensing unit guard size Split 42-71/ Sky Air 35-250
K.CGS	Condensing unit guard size 20-35
K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
K.DT1	Condensate drip tray for use with K.CWB90-2
KLIC-DD*	KNX interface for Split type systems
KRP413A15*	Adaptor PCB for remote on/off control - constant/pulse contact
KRP928A25*	Adaptor PCB for interface to Daikin centralised control systems

## Notes & Features:

- > All fan coils are supplied with infrared remote controller ARC466A58
- > New fan with Coanda effect for optimum air distribution and indoor comfort
- > New grid eye sensor redirects air away from the occupants in the room
- > Flash Streamer helps improving the indoor air quality

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

**Daikin Airconditioning UK Limited** The Heights Brooklands Weybridge Surrey KT13 0NY Tel 01932 879000 [daikin.co.uk](http://daikin.co.uk)