

SAMSUNG



Samsung WindFree™ Elite R32

The Samsung WindFree™ range keeps you comfortably cool without any cold drafts. It provides intelligent indoor climate comfort thanks to smart controls that adapt to your personal preferences, automatically maintaining optimal conditions.

WindFree™ Cooling

WindFree™ technology enhances your indoor comfort by using thousands of micro-holes to disperse fresh air uniformly without any unpleasant blasts of cold wind. In WindFree™ mode, air is spread softly and silently, creating a 'Still Air' environment¹ that provides you total well-being day and night.

Smart Operation

AI Auto Comfort² introduces you to an intelligent way of living. It analyses your room conditions and usage patterns³, and then automatically adjusts the temperature. Temperatures can also be managed remotely using the SmartThings App⁴. Turning it on and off, selecting the cooling mode or scheduling its operation is just one touch away.

WiFi Control

Temperatures in your building can be managed remotely using the SmartThings App⁵. Turning it on and off, selecting the cooling mode, scheduling its operation or monitoring the power consumption is just one touch away. The Bixby 2.0 Artificial Intelligence (AI) system⁶ analyses and predicts your needs so it can suggest the best settings for inside your home.

¹ASHRAE (American Society of Heating, Refrigerating, and Air-Conditioning Engineers) defines 'Still Air' as air currents at speeds below 0.15m/s which lacks the presence of cold drafts.

²A Wi-Fi connection and Samsung SmartThings application account are required.

³Stores user data, preferences and usage patterns to suggest the most useful options.

⁴Available on Android and iOS devices. A Wi-Fi connection and Samsung SmartThings application account are required.

⁵Available on Android and iOS devices. A Wi-Fi connection and Samsung SmartThings account are required.

⁶Voice control is supported in English.

Samsung WindFree™ Elite R32

- Three-step cooling: Fast Cooling mode, Dehumidification mode and WindFree™ Cooling mode.
- Tri-Care Filter system with Zeolite Coating.
- AI Auto Comfort and Motion Detect Sensor.
- Wi-Fi Control with Samsung SmartThings and Bixby voice controls.
- Compressor with Digital Inverter Boost technology.
- Triple Protector Plus to protect compressor, fan and controller from power surges.



Specifications

Model No.	Indoor Unit		AR09TXCAAWKNEU		AR12TXCAAWKNEU	
	Outdoor Unit (1-phase)		AR09TXCAAWKXEU		AR12TXCAAWKXEU	
Capacity	Cooling	kW	2.50(0.90-3.60)		3.50(0.90-4.80)	
	Heating		3.2 (0.8-7.10)		4.00(0.80-7.30)	
UK Capacity	Sensible cooling		2.31		2.69	
			4.63		3.95	
Efficiency	EER		4.74		4.26	
	COP ¹					
	SEER ¹		8.8/ A+++		8.5/ A+++	
	SCOP ¹		5.1/ A+++		5.1/ A+++	
Annual Energy Consumption	Cooling	kWh/a	99		144	
	Heating		631		659	
Sound Pressure	Indoor (H/Silent)		38/16		40/16	
	Outdoor (Cooling/Heating)		45		46	
Sound Power	Indoor Unit		56		58	
	Outdoor Unit		59		62	
Airflow Rate	Indoor	Cooling (T/H/M/L)	185/168/143/118		202/177/152/118	
		Heating (T/H/M/L)	218/202/177/152		218/193/168/135	
	Outdoor		750		750	
Dimensions (W x H x D)	Indoor		889 x 299 x 215		889 x 299 x 215	
	Outdoor		790 x 548 x 285		790 x 548 x 285	
Net Weight	Indoor Unit		10.6		10.6	
	Outdoor Unit		32.5		32.5	
Refrigerant	Pipe Size Gas		3/8		3/8	
	Liquid		1/4		1/4	
	Std/Max Pipe Length (Height)		3/15/(8)		3/15/(8)	
	Pre Charge to		5		5	
	Factory Charging		0.97		0.97	
	Additional Charge		15		15	
Electrical	CO ₂ Equivalent (R32 - GWP 675)		0.65		0.65	
	Power Supply		220-240 V, 50 Hz		220-240 V, 50 Hz	
	Power Input	Cooling	0.18 0.54/0.93		0.18/0.885/1.45	
		Heating	0.15/0.675/2.16		0.15/0.94/2.28	
	Current Input	Cooling	1.2/2.9/4.5		1.2/4.1/6.4	
		Heating	1.0/3.4/9.5		1.0/4.4/10.0	
Interconnecting Communication Cable		mm ²		Screened 0.75-1.5mm ² , 2 Core, F1 F2 Connection		

¹ Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

Accessories

Wireless Remote Controller	Premium Wired Controller	Sub PCB to Connect Wired Remote Controller	Touch Controller
(included)	MWR-WG00JN	MIM-A00N	MWR-SH11N