



Stylish
Where innovation meets creativity

FTXA-A(W/S/T) / RXA-A

R-32 BLUEEVOLUTION

Award winning design

Stylish brings together excellent design and technology to deliver a total climate solution for any interior. Measuring only 189mm deep, Stylish is one of the slimmest wall mounted units on the market and achieves the best in comfort, energy efficiency, reliability and control.

Inspired by its predecessors, Daikin Emura and Ururu Sarara, Stylish has earned the Good Design Award for its innovative look and functional capabilities.

Users can choose from **three distinct colours** (white, silver and blackwood).

- > **Curved corners** create an unobtrusive and space-saving design
- > Simple panel enables variation in texture and colour to easily blend into any room

The Coanda effect

Already present in the Ururu Sarara, the **Coanda effect** optimises the airflow for a comfortable climate. By using specially designed louvres, a more focused airflow allows a better temperature distribution throughout the whole room.

How it works

Stylish determines the airflow pattern based on whether the room needs heating or cooling. When Stylish is in heating mode, two louvres will direct air downward (vertical airflow), while in cooling mode the louvres will move air upward (ceiling airflow).

By creating two different airflow patterns, Stylish prevents draughts and establishes a more stable and comfortable room temperature for occupants.

Fresh, pure air

Stylish provides the best indoor air quality using **Daikin's Flash Streamer** technology. This system removes particles, allergens and odours to deliver healthy indoor air.

Quiet operation

Stylish uses a **newly designed fan** to optimise airflow for higher energy efficiency at low sound levels. To achieve higher energy efficiency, Daikin designed a new fan that runs efficiently within Stylish's compact dimensions. Together, the fan and heat exchanger attain top energy performance but operate at a sound level that is practically inaudible to occupants.



FTXA-AW



FTXA-AS



FTXA-AT



RXA-A



ARC466A58



WI-FI ADAPTOR
INCLUDED AS STANDARD



FTXA-A(W/S/T) / RXA-A

R-32 BLUEEVOLUTION

Indoor Units	White	FTXA15AW	FTXA20AW	FTXA25AW	FTXA35AW	FTXA42AW	FTXA50AW							
	Silver	FTXA15AS	FTXA20AS	FTXA25AS	FTXA35AS	FTXA42AS	FTXA50AS							
	Blackwood	FTXA15AT	FTXA20AT	FTXA25AT	FTXA35AT	FTXA42AT	FTXA50AT							
Capacity	UK Total Cooling	Multi Combination Only						4.56						
	UK Sensible Cooling							4.11						
	Nominal Cooling							5.0						
	Nominal Heating							5.8						
Seasonal Efficiency (EN14825) COOLING	Energy Label	Multi Combination Only						A++						
	Pdesign							5.0						
	SEER							7.33						
	Annual Energy Consumption							239						
Seasonal Efficiency (EN14825) HEATING	Energy Label	Multi Combination Only						A++						
	Pdesign							4.00						
	SCOP							4.6						
	Annual Energy Consumption							1217						
Nominal Efficiency	EER/COP	Multi Combination Only						3.68/4.00						
Air Flow Rate (Cooling)	High / Nom / Low / Silent							m ³ /sec	0.183/0.136/0.101/0.076	0.183/0.136/0.101/0.076	0.191/0.143/0.101/0.076	0.198/0.143/0.101/0.076	0.218/0.163/0.120/0.076	0.225/0.173/0.126/0.086
Dimensions	Height / Weight / Depth							mm	295 x 798 x 189					
Weight								kg	13	13	13	13	13	13
Sound Pressure (Cooling)	High / Nom / Low / Silent	dbA	39/32/25/19	39/32/25/19	40/33/25/19	41/33/25/19	45/37/29/21	46/39/31/24						
Sound Power (Cooling)		dbA	57	57	57	60	60	60						
Outdoor Units			RXA20A	RXA25A	RXA35A	RXA42A	RXA50A							
Dimensions	Height x Width x Depth	mm	550 x 765 x 285	550 x 765 x 285	550 x 765 x 285	735 x 825 x 300	735 x 825 x 300							
Weight		kg	32	32	32	47	47							
Electrical Details	Power Supply		1ph	1ph	1ph	1ph	1ph							
	Running Current	A	-	-	-	-	-							
	Starting Current	A	-	-	-	-	-							
	Max Fuse Size	A	10	13	13	16	16							
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5							
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 1/2 (12.7)							
Pipework	Maximum Length	m	20	20	20	30	30							
	Maximum Vertical Rise	m	15	15	15	20	20							
	Precharged to	m	10	10	10	10	10							
	Additional charge	g/m	20	20	20	20	20							
	Holding charge	kg	0.76	0.76	0.76	1.3	1.3							
Sound Pressure (Cooling)	High	dBA	46	46	49	48	48							
Sound Power (Cooling)		dBA	59	59	61	62	62							
Operating Range (Cooling)	Min / Max	°CDB	-10/46	-10/46	-10/46	-10/46	-10/46							
Operating Range (Heating)	Min / Max	°CWB	-15/18	-15/18	-15/18	-15/18	-15/18							
ECA Eligible			●	●	●	●	●							

Accessory Ref	Description
EKRS21	Wire harness for new S21 port for all marked (*) options
BRC073*	Optional wired remote controller BRC1E53 style - Connection cable required
BRCW901A03	3m connection cable for BRC073
BRCW901A08	8m connection cable for BRC073
K.CGM	Condensing unit guard size 42-71
K.CGS	Condensing unit guard size 20-35
K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
K.DT1	Condensate drip tray for use with K.CWB90-2
KLIC-DD*	KNX interface for Split type systems
KRP413A15*	Adaptor PCB for remote on/off control - constant/pulse contact
KRP928A25*	Adaptor PCB for interface to Daikin centralised control systems

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com