



SINGLE-SPLIT WALL MOUNTED TYPE

Standard Series **SRK-ZSP-W**

NEW




SRK25ZSP-W, SRK35ZSP-W, SRK45ZSP-W



Wireless remote control



SRC25ZSP-W
SRC35ZSP-W



SRC45ZSP-W



SRK-ZSP-W series can be selected for use both R32 and R410A outdoor unit.



Elegant Timeless Design

ZSP series is elegant design fits into any kind of interior decoration.

Energy Class Improvement

All class **A++**

Compact and Light weight

The SRK-ZSP-W series offers great installation flexibility.

FUNCTIONS

Energy saving

Air flow

Clean operation & Filter



Comfort & Convenience

Others



SPECIFICATIONS

Indoor unit				SRK25ZSP-W	SRK35ZSP-W	SRK45ZSP-W
Outdoor unit				SRC25ZSP-W	SRC35ZSP-W	SRC45ZSP-W
Power source				1 Phase, 220 - 240V, 50Hz		
Nominal cooling capacity (Min~Max)		kW		2.5(0.9~3.1)	3.2(0.9~3.7)	4.5(1.3~4.8)
Nominal heating capacity (Min~Max)		kW		2.8(1.0~4.1)	3.6(1.0~4.6)	5.0(1.2~5.8)
Power consumption		kW		0.710 / 0.690	0.910 / 0.930	1.350 / 1.360
EER/COP		Cooling/Heating		3.52/4.05	3.52 / 3.87	3.33 / 3.68
Max. running current		A		9	9	14.5
Sound power level	Indoor	Cooling/Heating	dB(A)	57 / 57	58 / 58	56 / 62
	Outdoor	Cooling/Heating		57 / 56	59 / 60	63 / 64
Sound pressure level	Indoor	Cooling (Hi/Me/Lo)		45 / 34 / 23	45 / 36 / 23	44 / 39 / 24
		Heating (Hi/Me/Lo)		43 / 34 / 26	44 / 36 / 28	48 / 41 / 30
		Outdoor		Cooling/Heating	47 / 45	48 / 48
Air flow	Indoor	Cooling (Hi/Me/Lo)		10.0 / 7.3 / 4.2	9.5 / 6.8 / 4.2	9.0 / 7.2 / 3.8
		Heating (Hi/Me/Lo)	9.5 / 7.3 / 5.2	9.6 / 7.4 / 5.5	12.0 / 9.2 / 6.2	
		Outdoor	Cooling/Heating	23.7 / 19.7	22.8 / 22.0	35.6 / 33.4
Exterior dimensions	Indoor			267 x 783 x 210		
	Outdoor	HeightxWidthxDepth	mm	540 x 645(+57) x 275		595 x 780(+62) x 290
Net weight		Indoor / Outdoor		kg	7.0 / 26.5	7.5 / 36.0
Refrigerant		Type/GWP		R32 / 675		
		Charge		kg/TCO ₂ Eq		1.10 / 0.743
Refrigerant piping size		Liquid/Gas		ø mm		6.35(1/4") / 9.52(3/8")
Refrigerant line (one way) length		Liquid		m		Max. 15
Vertical height differences		Outdoor is higher/lower		m		Max. 10 / Max. 10
Outdoor operating temperature range		Cooling		°C		
		Heating		-15~46		
Clean filter				-15~24		

* The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.